

BUILT BY PROS FOR PROS **LAWN TRACTOR**

KUTTER®



A new design, the highest quality, and many years of manufacturing experience make this lawn tractor the perfect companion for your garden

Liaocheng JADE Outdoor Power Equipment Co., Ltd

LAWN TRACTOR

34/36/40/42 R
THE PINNACLE OF LAWN CARE
REAR CLIPPING CHUTE



R/Rear Discharge

Mow your lawn to perfection with this top-of-the-line premium lawn tractor. With excellent all-wheel drive traction and an efficient 42" mower deck, you can get the job done quickly.



42S

S/Side Discharges

Lawn Tractor with 42-in. Deck

Your lawn is something to be proud of. So make the most of your mowing time when the grass is tall with a trustworthy lawn tractor that can handle any job on your lawn. With attachments for every season, you can shred, haul and bag your way to a perfect lawn.

Effective Side Discharge - This system ensures that grass is dispersed quickly and evenly, making your mowing process smooth and easy.





LAWN TRACTOR

LT 40R

34R
36R
42S/R

	Displacement	Horsepower
34R	385cc	11.5HP
36R	439cc	13HP
40R	586cc/680cc	15/23HP
42S/R	586cc/680cc	15/23HP

- ✓ ZONSEN XP680 II 23HP/LC2P73F-A V-Twin 15HP
- ✓ Flexible steering
Motion control levers are shaped and positioned for operator comfort and ease of control



COMPACT DESIGN

High Power And Torque

ZONSEN XP680 II 23HP

(OPTIONAL) LC2P73F-A V-Twin 15HP

7000m²
Maximum Working Area



Deck Height Adjustment
Minimizing workload, Adjustment of mowing height increments is precise enough



Rugged Frame
The pedal foot control easily switches from forward to reverse to effortlessly change speed and direction.



320 LITER COLLECTOR

With rear-row grass bag suspension device, the grass bag has large capacity and high collection efficiency. When mowing, the grass clippings go directly into the grass collecting bag without manual intervention, and the lawn is instantly clean and tidy.

ADVANCED INTEGRATED TRANSMISSION

No matter the challenge, the upgraded transmission drives your forward with maximum force.



SPEED
3000/1800 rpm



OUTPUT TORQUE
156/291Nm



Hydro-Gear
T2

Data source Hydro-Gear official website

MOWING TO A FASTER FINISH



Designed to withstand tough working conditions, it is equipped with top-of-the-line ergonomic features and comfortable operator functions so you can fully focus on meticulous cutting results.



Model Number		LT-34R (Promotion)	LT-36R	LT-40R
ENGINE	Engine	ZONSEN XP380A 11.5HP	ZONSEN XP440E 13HP	LC2P73F-A V-Twin 15HP ZONSEN XP680 II 23HP
	Displacement	382cc	439cc	586cc/680cc
	Oil Capacity	8L	8L	8L
DECK	Number of Blades	2	2	2
	Height Range	1.18-3.15inch/30 – 80 mm	1.18-3.15inch/30 – 80 mm	1.18-3.15inch/30 – 80 mm
	Minimum Uncut Radius	39.37inch/1000mm	39.37inch/1000mm	39.37inch/1000mm
	Cutting Width	34inch/860mm	36inch/915mm	40inch/1020mm
	Reverse Mowing	Yes	Yes	Yes
DRIVE SYSTEM	Drive Type	Hydrostatic	Hydrostatic	Hydrostatic
	Ground Speed	FWD 0-7KPH/REV 0-4KPH	FWD 0-7KPH/REV 0-4KPH	FWD 0-7KPH/REV 0-4KPH
	Steering Wheel	Premium With Soft Grip	Premium With Soft Grip	Premium With Soft Grip
	Anti-scalp Wheels	2	2	2
	Tyres	15x6.00-6 (F) - 18x8.5-8 (R)	15x6.00-6 (F) - 18x8.5-8 (R)	15x6.00-6 (F) - 18x8.5-8 (R)
DIMENSIONS	Length/Width/Height	2330mm*930mm*1100mm	2330mm*980mm*1100mm	2330 mm*1080 mm*1100mm
	Container Load 40HQ	42pcs	42pcs	42pcs
	Container Load 20GP	12pcs	12pcs	12pcs
FEATURES	Headlight	LED	LED	LED
	Hour Meter	Yes	Yes	Yes
	Collector Emptying	Manual	Manual	Manual
	Collector Capacity	320 L	320 L	320 L
	Washing Connection	Yes	Yes	Yes
	Collector Type	Textile	Textile	Textile
	Cup Holder	Yes	Yes	Yes
	Safety System	Seat with Safety Contact Breaker	Seat with Safety Contact Breaker	Seat with Safety Contact Breaker

ALL SPECIFICATIONS

LAWN TRACTOR

Model Number		LT-42R	LT-42S
ENGINE	Engine	LC2P73F-A V-Twin 15HP ZONSEN XP680 II 23HP	LC2P73F-A V-Twin 15HP ZONSEN XP680 II 23HP
	Displacement	586cc/680cc	586cc/680cc
	Oil Capacity	8L	8L
DECK	Number of Blades	2	2
	Height Range	1.18-3.15inch/30 – 80 mm	1.18-3.15inch/30 – 80 mm
	Minimum Uncut Radius	39.37inch/1000mm	39.37inch/1000mm
	Cutting Width	42inch/1070mm	42inch/1070mm
DRIVE SYSTEM	Reverse Mowing	Yes	Yes
	Drive Type	Hydrostatic	Hydrostatic
	Ground Speed	FWD 0-7KPH/REV 0-4KPH	FWD 0-7KPH/REV 0-4KPH
	Steering Wheel	Premium With Soft Grip	Premium With Soft Grip
	Anti-scalp Wheels	2	2
	Tyres	15x6.00-6 (F) - 18x8.5-8 (R)	15x6.00-6 (F) - 18x8.5-8 (R)
DIMENSIONS	Length/Width/Height	2330mm*1150 mm*1100mm	1300mm*1150 mm*1100mm
	Container Load 40HQ	42pcs	42pcs
	Container Load 20GP	12pcs	12pcs
FEATURES	Headlight	LED	LED
	Hour Meter	Yes	Yes
	Collector Emptying	Manual	NO
	Collector Capacity	320 L	NO
	Washing Connection	Yes	Yes
	Collector Type	Textile	NO
	Cup Holder	Yes	Yes
	Safety System	Seat with Safety Contact Breaker	Seat with Safety Contact Breaker



switch to snow removal in winter

Our comfortable, reliable, easy-to-use line-up is loaded with features that keep your lawn looking sharp and help handle loads of other projects — even snow removal — season after season, year after year.



**Robot Welding (tolerance $\leq 0.5\text{mm}$, 100% consistency);
Electrophoretic Coating + Powder Spraying.**

✔ **Salt Spray Test:**
1,500 hours without rust spots (vs. GB standard 800 hours)



**CUP HOLDERS IN THE FENDER NEXT TO
THE DRIVER'S SEAT**



FRONT BUMPER PROTECTS THE TRACTOR

Additional front-end protection Attractive, bold style



FRONT AND REAR GRASS TIRES

The grass tires on the LT 40CS mower provide excellent turf protection and traction, even on slopes and sharp turns.

LAWN CRUISERS

Performance that's so enjoyable you won't want to stop.

Actual product may differ from photos.

BORN FOR LANDSCAPING



Lawn Aerator



Stand On Leaf Blower



Wood Chipper

Liaocheng JADE Outdoor Power Equipment Co., Ltd

Andy Xu

+86 133 5446 6866
andyxu@jadeequipments.com

Alice Feng

+86 132 5642 9315
frx@jadeequipments.com

Grace Si

+86 152 7588 1673
grace@jadeequipments.com

Selina Yu

+86 176 6356 1716
selinayu@jadeequipments.com

Fila Liu

+86 132 8759 1357
fila@jadeequipments.com

Address Yuji Industrial Park, Yuji Town, Jiangbei Watertown Tourism Resort, Liaocheng City