BUILT BY PROS FOR PROS





A new design, the highest quality, and many years of manufacturing experience make this lawn tractor the perfect companion for your garden

Liaocheng JADE Outdoor Power Equipment Co., Ltd



LAWN MOWING















SOIL, TURF & GROUNDS













TURFHOME&GARDEN









CAREGOLF &SPORTS







34/36/40/42 R THE PINNACLE OF LAWN CARE REAR CLIPPING CHUTE

S:Rear Discharge

R/Rear Discharge

Mow your lawn to perfection with this top-of-the-line premium lawn tractor. With excellent all-wheel drive traction and an efficient 42" mower deck, you can get the job done quickly.









425

S/Side Discharges

BIG JOBS REQUIRE BIG POWER

Your lawn is something to be proud of. So make the most of your mowing time when the grass is tall with a trustworthy lawn tractor that can handle any job on your lawn. With attachments for every season, you can shred, haul and bag your way to a perfect lawn.

Effective Side Discharge - This system ensures that grass is dispersed quickly and evenly, making your mowing process smooth and easy.











COMPACT DESIGN

Easy to tow and excellent maneuverability The 40-inch mowing deck is perfect for narrow paths and gated entrances

Better slope performance •

More operator comfort over uneven ground.





Heavy duty rubber discharge chute

The discharge chute is built of heavy-duty rubber to withstand wear and tear while protecting nearby property.





One-piece hood with quality headlights

Molded-in color material reduces sound and will not rust or dent, The hood opening allows plenty of cooling air to enter while keeping noise levels low.

For increased visibility and safer use



Anti-Scalp Wheels

Reduces the risk of scalping uneven lawns



Easy, Comfortable Steering

Oversized and soft-touch steering wheel delivers a comfortable driving experience



REINFORCED (1)



A stamped deck built with strong materials and an exceptional belt design while delivering a premium cut.

Number of blades

Two Pieces

Cutting width

Cutting height rang

34-42inch/860-1070mm 1.18-3.54inch/38-114mm



320 LITER

COLLECTOR

With rear-row grass bag suspension device, the grass bag has large capacity and high collection efficiency. When mowing, the grass clippings go directly into the grass collecting bag without manual intervention, and the lawn is instantly clean and tidy.

TRANSMISSION

No matter the challenge, the upgraded transmission drives your forward with maximum force.



SPEED 3000/1800 rpm



OUTPUT TORQUE



Data source Hydro-Gear official website





WIDE FOOTSTOOL WITH DEBRIS REMOVAL CHANNEL

Robot Welding (tolerance ≤ 0.5mm, 100% consistency); Electrophoretic Coating + Powder Spraying.

Salt Spray Test: 1,500 hours without rust spots (vs. GB standard 800 hours)

Weatherability:

QUV accelerated aging for 3,000 hours, color difference $\Delta E < 1.5$

Large footstool makes it easier to straddle the mower deck when entering or leaving your seat



CUP HOLDERS IN THE FENDER NEXT TO THE DRIVER'S SEAT



Additional front-end protection Attractive, bold style



FRONT AND REAR GRASS TIRES

The grass tires on the LT 40CS mower provide excellent turf protection and traction, even on slopes and sharp turns.

LAWN CRUISERS

Performance that's so enjoyable you won't want to stop.



LT 40 R 34R 36R 42S/R

	Displacement	Throttle
34R	622cc	17HP
36R	622cc	17HP
40R	679сс	23HP
42S/R	679сс	23HP

Zonsen XT680 23HP V-Twin

Flexible steering

Motion control levers are shaped and positioned for operator comfort and ease of control







COMPACT DESIGN

High Power And Torque

Zonsen XT680 V-Twin

(OPTIONAL) Loncin

6800-7200 m² Maximum Working Area



Deck Height Adjustment

Minimizing workload, Adjustment of mowing height increments is precise enough



Rugged Frame

The pedal foot control easily switches from forward to reverse to effortlessly change speed and direction.



ALL SPECIFICATIONS

Zero Turn Mower

	Model Number	LT-34R	LT-36R	LT-40R	LT-42R/S	LT-48CS
ENGINE	Engine	Zonsen XP440E 13HP	Zonsen XP440E 13HP	Ioncin LC2P73F-A V-Twin	loncin LC2P73F-A V-Twin	Zonsen XP680 23Hp
	Displacement	439cc	439cc	586cc	586cc	679cc
	Oil Capacity	9L	9L	9L	9L	9L
DECK	Number of Blades	2	2	2	2	2
	Height Range	1.18-3.54inch/30 – 90 Mm	1.18-3.54inch/30 – 90 Mm	1.18-3.54inch/30 – 90 Mm	1.18-3.54inch/30 – 90 Mm	/
	Minimum Uncut Radius	39.37inch/1000mm	39.37inch/1000mm	39.37inch/1000mm	39.37inch/1000mm	39.37inch/1000mm
	Cutting Width	34inch/860mm	36inch/910mm	40inch/1020mm	42inch/1070mm	42"(1066MM)/48" (1219mm)/50"(1270mm
	Reverse Mowing	Yes	Yes	Yes	Yes	Yes
	Drive Type	Hydro Gear T2/Loncin HT2E	Hydrostatic With Auto Lok™ Diff			
	Ground Speedg	FWD 0-7KPH/REV 0-4KPH	FWD 0-7KPH/REV 0-4KPH	FWD 0-7KPH/REV 0-4KPH	FWD 0-7KPH/REV 0-4KPH	FWD 0-7KPH/REV 0-4KPH
DRIVE SYSTEM	Steering Wheel	Premium With Soft Grip				
	Antiscalp Wheels	2	2	2	2	2
	Tyres	15x6.00-6 (F) - 18x8.5-8 (R)	15x6.00-6 (F) - 18x9.5-8 (R			
	Length/Width/Height	2330 mm*930mm*1010mm	2330 mm*980mm*1010mm	2330 Mm*1050mm*1010mm	Side Discharge:1300mm*1150mm*1010mm Rear Discharge: 2330 mm*1150mm*1010mm	/
Š	Package Dimensions	1700mm*1160mm*840mm	1700mm*1160mm*840mm	1700mm*1160mm*840mm	1800mm*1160mm*840mm	/
	Weight	206 Kg	208 Kg	210 Kg	Rear Discharge: 212kg/ Side Discharge:206kg	255kg
ISIO	Packing Weight	20kg	20kg	20kg	20kg	/
DIMENSIONS	Container Load 40HQ	42pcs	42pcs	42pcs	42pcs	/
۵	Container Load 20GP	12pcs	12pcs	12pcs	12pcs	/
	Headlight	LED	LED	LED	LED	LED
	Hour Meter	Yes – On Display	Standard			
	Collector Emptying	Manual	Manual	Manual	Rear Discharge: 320I//side Discharge: No	/
FEATURES	Collector Capacity	320 L	320L	320 L	Rear Discharge: Textile//side Discharge: No	/
	Washing Connection	Yes	Yes	Yes	Yes	/
	Collector Type	Textile	Textile	Textile	Rear Discharge: Textile//side Discharge: No	/
	Cup Holder	Yes	Yes	Yes	Yes	/
	Safety System	Seat With Safety Contact Breaker	/			